





RoHS



P.C.B LAYOUT

- SPECIFICATIONS**
- Voltage rating: 100V AC, DC
 - Current rating: 2A, AC, DC
 - Withstanding Voltage: 800V AC/minute
 - Insulation resistance: 1000MΩ min
 - Temperature range: -25° C~+85° C
 - Contact resistance: 20mΩ max
- WAFER**
- Part No.: W2001RB-NP-B
 - Poles : 02-16P
 - Housing Material: PA66 UL94V-0
 - Pin Material: Brass
 - Contact Area Plating: Tin-Plated
 - The Dimension Marked “▼” Must Be Recorded

Poles	Dimension (mm)		
	A	B	C
02	2.00	6.00	5.00
03	4.00	8.00	7.00
04	6.00	10.00	9.00
05	8.00	12.00	11.00
06	10.00	14.00	13.00
07	12.00	16.00	15.00
08	14.00	18.00	17.00
09	16.00	20.00	19.00
10	18.00	22.00	21.00
11	20.00	24.00	23.00
12	22.00	26.00	25.00
13	24.00	28.00	27.00
14	26.00	30.00	29.00
15	28.00	32.00	31.00
16	30.00	34.00	33.00

XYDZ® 东莞市祥运连接器有限公司
 Dongguan XiangYun Connectors CO., Ltd

更新图面		2019-06-03	陈雄军	更新图面	2019-06-03	陈雄军	一般公差 GENERAL TOLERANCE: 0±0.30 .00±0.25 .000±0.05 ANGLE: ±1°	投影法 Projection MM	品名 (PART NAME)	PH 2.00mm 90° Wafer Connector Series	料号 (PART NO)	W2001RB-NP-B	状态码 C
修订版本		2015-11-04	陈雄军	变更图宽格式内容	2013-12-27	陈雄军	绘图/DR P.C. Draw	单位 Unit MM					
新版本		2011-05-24	陈雄军	说明	2011-05-24	陈雄军	审核/CHKC 审核/CHKC	比例/Scale 1:1					
DESCRPTION			承认	日期		承认	核准/APPRO 核准/APPRO	页码/SHEET 1/1					
DATE:			APPRO.			APPRO.	日期/DATE	版本/Rev D					