



- ### SPECIFICATIONS
- Voltage rating: 250V AC, DC
  - Current rating: 3A, AC, DC
  - Withstanding Voltage: 800V AC/minute
  - Insulation resistance: 1000MΩ min
  - Temperature range: -25°C ~ +85°C
  - Contact resistance: 20mΩ max
- WAFER
- Part No. : W2013SR-NP
  - Poles : 02~16P
  - Housing Material : PA9T UL94V-0, Natural
  - Pin Material : Brass
  - Solder Tabs Material : Brass
  - Contact Area Plating: Tin-Plated
  - The Dimension Marked “▼” Must Be Recorded

Poles	Dimensions (mm)		
	A	B	C
02	2.00	8.00	4.50
03	4.00	10.00	6.50
04	6.00	12.00	8.50
05	8.00	14.00	10.50
06	10.00	16.00	12.50
07	12.00	18.00	14.50
08	14.00	20.00	16.50
09	16.00	22.00	18.50
10	18.00	24.00	20.50
11	20.00	26.00	22.50
12	22.00	28.00	24.50
13	24.00	30.00	26.50
14	26.00	32.00	28.50
15	28.00	34.00	30.50
16	30.00	36.00	32.50

一般公差 GENERAL TOLERANCE:	0±0.30 .00±0.25 .000±0.20 ANGLE: ±1°
绘图/DR	P.P. Duwa
审核/CHECK	陈雄军
核准/APPRO	胡进
日期/DATE	2019-06-03

**XYDZ® 东莞市祥运连接器有限公司**  
Dongguan XiangYun Connectors CO., Ltd

更新图面	2019-06-03	P.P. Duwa	承认	2019-06-03	投影法 Projection	品名 (PART NAME)	PA2.00mm SMT 90° Wafer Connector Series	料号 (PART NO)	W2013SR-NP	状态码	C
新版本	2018-10-10	P.P. Duwa	承认	2019-06-03	单位 Unit						
说明					大小/Size						
版次					页码/Sheet						
REV.					版本/Rev						