



Poles	Dimensions (mm)		
	A	B	C
2x01	--	6.65	4.30
2x02	3.00	9.65	7.30
2x03	6.00	12.65	10.30
2x04	9.00	15.65	13.30
2x05	12.00	18.65	16.30
2x06	15.00	21.65	19.30
2x07	18.00	24.65	22.30
2x08	21.00	27.65	25.30
2x09	24.00	30.65	28.30
2x10	27.00	33.65	31.30
2x11	30.00	36.65	34.30
2x12	33.00	39.65	37.30

- ### ■ SPECIFICATIONS
- Voltage rating: 250V AC, DC
  - Current rating: 5A, AC, DC
  - Withstanding Voltage: 1500V AC/minute
  - Insulation resistance: 1000MΩ min
  - Temperature range: -40°C~+105°C
  - Contact resistance: 20mΩ max
- ### ■ WAFER
- Part No.: W3045SVD-2xNP-Y
  - Poles : 02-24P
  - Housing Material: LCP UL94V-0 Black
  - Ter Material: Brass
  - Solder Tabs Material: Brass
  - Contact Area Plating: Matte Tin Plating
  - Cap:Stainless Steel
- The Dimension Marked “▼” Must Be Recorded

**XYDZ® 东莞市祥运连接器有限公司**  
 Dongguan XiangYun Connectors CO., Ltd

D	更新图画	2019-06-03	陈雄军	一般公差 GENERAL TOLERANCE: ANGLE: ±1°	0±0.30 .0±0.25 .000±0.20 .000±0.05	陈雄军	胡进	2019-06-03	版本/Rev	D
C	修订版本	2015-11-04	陈雄军	绘图/DR	0±0.30 .0±0.25 .000±0.20 .000±0.05	陈雄军	胡进	2019-06-03	版本/Rev	D
B	变更图宽格式内容	2013-12-27	陈雄军	审核/CHKC	0±0.30 .0±0.25 .000±0.20 .000±0.05	陈雄军	胡进	2019-06-03	版本/Rev	D
A	新版本	2011-05-24	陈雄军	核准/APPRO	0±0.30 .0±0.25 .000±0.20 .000±0.05	陈雄军	胡进	2019-06-03	版本/Rev	D
H	版次 REV.	说明 DESCRIPTION	日期 DATE	承认 APPRO.	日期/DATE	日期/DATE	日期/DATE	日期/DATE	日期/DATE	日期/DATE

投影法 Projection	品名 (PART NAME)	料号 (PART NO)	状态码
MM	Mollex 3.0mm SMT 180° 鱼叉式 Wafer Connector Series	W3045SVD-2xNP-Y	C