RoHS





W4001SR-03N01





W4001SR-05N03





W4001SR-05N02





W4001SR-07N05



■ SPECIFICATIONS

- Voltage rating: 600V AC, DC
- Current rating: 1A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance:1000MΩ min
- Temperature range: -25° C~+85° C
- Contact resistance: 20mΩ max

■ WAFER

- Part No.: W4001SR-NP
- Poles : 03-09P
- Housing Material: PA6T UL94V-0
- Pin Material: Brass
- Contact Area Plating: Tin-plated
- The Dimension Marked "▼" Must Be Recorded





4003WR-07N04L





W4001SR-07N04





W4001SR-07N03





W4001SR-09N04





P.C.B LAYOUT



PART NO.	Dimensions(mm)		
	A	B	C
W4001SR-03N01	4.00	10.00	6.80
W4001SR-05N02	8.00	14.00	10.80
W4001SR-05N03	8.00	14.00	10.80
W4001SR-07N05	12.00	18.00	14.80
W4001SR-07N04L	12.00	18.00	14.80
W4001SR-07N04	12.00	18.00	14.80
W4001SR-07N03	12.00	18.00	14.80
W4001SR-09N04	16.00	22.00	18.80

版次 REV.	说明 DESCRIPTION	日期 DATE.	承认 APPRO.
D	更新图面	2019-06-03	PH.Duan
C	修订版本	2015-11-04	陈雄军
B	变更图宽格式内容	2013-12-27	陈雄军
A	新版本	2011-05-24	陈雄军

一般公差 GENERAL TOLERANCE:	0±0.30 .0±0.25 .00±0.20 .000±0.05 ANGLE. ±1°
绘图/DR	PH.Duan
审核/CHECK	陈雄军
核准/APPRO	胡 进
日期/DATE	2019-06-03

XYDZ® 东莞市祥运连接器有限公司
Connectors DongGuan XiangYun Connectors CO.,Ltd

投影法 Projection		品 名 (PART NEME)	BH4.00mm SMT 90° Wafer Connector Series
单位 Unit	MM		
比例/Scale	1:1		
大小/SIZE	A4	料 号 (PART NO)	W4001SR-NP
页码/SHEET	1/1		状态码 C
版本/Rev	D		