



PCB LAYOUT: TOP VIEW
TOLERANCE: ±0.05mm
RECOMMENDED PCB THICKNESS: 1.78 MAX

■ SPECIFICATIONS

- Voltage rating: 600V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩ min
- Temperature range: -25°C~+85°C
- Contact resistance: 20mΩ max
- WAFER
 - Part No.: W4202LTD-2x12P-JCB
 - Poles : 24P
 - Housing Material: PA66 UL94V-0 Natural
 - Pin Material: Brass
 - Contact Area Plating: Matte Tin-Plated
 - Mates With: H4201 dual row receptacle
- The Dimension Marked “▼” Must Be Recorded

更新图面		2019-07-03	段平会	段平会	一般公差 GENERAL TOLERANCE:		0±0.30 -0±0.25 .00±0.20 .000±0.10	投影法 Projection		品名 (PART NAME)		Molex 4.20mm 180° 空芯喇叭口 Wafer Connector Series	
变更公差		2018-09-06	段平会	段平会	绘图/DR		0±0.30 -0±0.25 .00±0.20 .000±0.10	单位 Unit		料号 (PART NO)		W4202LTD-2x12P-JCB	
新版本		2018-06-11	段平会	段平会	审核/CHECK		ANGLE: ±1°	比例/Scale		状态码		C	
说明		2019-07-03	承认	承认	批准/APPRO		ANG	大小/SIZE					
版次		说明	日期	承认	日期/DATE		ANG	页码/SHEET					
REV.		DESCRIPTION	DATE	APPRO.	2019-07-03		ANG	版本/REV					

XYDZ® 东莞市祥运连接器有限公司
Dongguan XiangYun Connectors CO., Ltd