



- ### ■ SPECIFICATIONS
- Voltage rating: 600V AC, DC
 - Current rating: 7A, AC, DC
 - Withstanding Voltage: 1500V AC/minute
 - Insulation resistance: 1000MΩ min
 - Temperature range: -25° C~+85° C
 - Contact resistance: 20mΩ max
- ### ■ WAFER
- Part No.: W42021VD-2xNP-B
 - Poles : 02-24P
 - Housing Material: PA66 UL94V-2 or UL94V-0
 - Pin Material: Brass
 - Contact Area Plating: Tin-Plated or Gold-Flash
 - Mates With: W4201VTD, H4201L and H4201 dual row receptacle
- The Dimension Marked “▲” Must Be Recorded

Part No.	Dimensions (mm)	
	A	B
2x01	4.20	10.80
2x02	8.40	15.00
2x03	12.60	19.20
2x04	16.80	23.40
2x05	21.00	27.60
2x06	25.20	31.80
2x07	29.40	36.00
2x08	33.60	40.20
2x09	37.80	44.40
2x10	42.00	48.60
2x11	46.20	52.80
2x12	50.40	57.00

D	更新图面	2019-07-03	陈雄军	更新图面
C	修訂版本	2015-11-04	陈雄军	修訂版本
B	变更图宽格式内容	2013-12-27	陈雄军	变更图宽格式内容
A	新版本	2011-05-24	陈雄军	新版本
H	说明	日期	承认	说明
1	DESCRPTION	DATE	APPRO.	REV.

一般公差 GENERAL TOLERANCE:	0±0.30 -0±0.25 .00±0.20 .000±0.05
ANGLE: ±1°	
绘图/DR	陈雄军
审核/CHECK	陈雄军
核准/APPRO	胡进
日期/DATE	2019-07-03

XYDZ® 东莞市祥运连接器有限公司
Dongguan XiangYun Connectors CO., Ltd

品名 (PART NAME): Molex 4.20mm 180° 特殊喇叭口 Wafer Connector Series

料号 (PART NO): W42021VD-2xNP-B

状态码: C