


RoHS






HSG Material / Color
 None:PA66-V2 Natural
 BK:PA66-V2 Black
 V0:PA66-V0 Natural
 V0BK:PA66-V0 Black
 LP:LCF-V0 Natural
 LPPBK:LCP-V0 Black
 9T:PA9T-V0 Natural
 9TBK:PA9T-V0 Black

Contact Finish
 None:Tin-Plated
 SW:Matte Tin-Plated
 G:Gold-Flash
 G3:3u" Gold
 G10:10u" Gold
 G15:15u" Gold

W4202V-2xNP-X X-WL12

- SPECIFICATIONS
- Voltage rating: 600V AC, DC
 - Current rating: 7A, AC, DC
 - Withstanding Voltage: 1500V AC/minute
 - Insulation resistance:1000MΩ min
 - Temperature range: -25° C~+85° C
 - Contact resistance: 20mΩ max
- WAFER
- Part No.: W4202V-2xNP-XX-WL12
 - Poles : 02-24P
 - Housing Material: PA66 UL94V-2 or UL94V-0
 - Pin Material: Brass
 - Contact Area Plating: Tin-Plated or Gold-Flash
 - PIN L=1, 14x22, 10
 - The Dimension Marked "▼" Must Be Recorded



PART NO.	Dimensions (mm)	
	A	B
2x01	--	5.60
2x02	4.20	9.80
2x03	8.40	14.00
2x04	12.60	18.20
2x05	16.80	22.40
2x06	21.00	26.60
2x07	25.20	30.80
2x08	29.40	35.00
2x09	33.60	39.20
2x10	37.80	43.40
2x11	42.00	47.60
2x12	46.20	51.80

CIRCUIT SIZE LAYOUT

P. C. B LAYOUT

D	更新图面	2019-07-03	陈雄军
C	修打版本	2015-11-04	陈雄军
B	变更图宽格式内容	2013-12-27	陈雄军
A	新版本	2011-05-24	陈雄军
H	版次 RRV.		

一般公差		0±0.30
GENERAL TOLERANCE:		.00±0.25
		.000±0.05
ANGLE: ±1°		
绘图/DR	陈雄军	2019-07-03
审核/CHECK	胡进	
批准/APPRO	胡进	
日期/DATE	2019-07-03	

XYDZ® 东莞市祥运连接器有限公司
 Dongguan XiangYun Connector's CO., Ltd

投影法: 单位: MM
 比例/Scale: 1:1
 大小/Size: A4
 页码/SHEET: 1/1
 版本/New: D

品名: Molex 4.20mm 180° Wafer
 (PART NAME)
 料号: W4202V-2xNP-XX-WL12
 (PART NO)
 状态码: C